

Submittal Data: ASU9RLF1



Job Name:	Location:			
Purchaser:				
Engineer:				
Submitted To:	For:	<input type="checkbox"/> Reference	<input type="checkbox"/> Approval	<input type="checkbox"/> Construction
Submitted By:				
Unit Designation:	Schedule No.	Model No.:		

Capacities:

Voltage/Frequency/Phase	208-230/60/1
Available Voltage Range	187-253VAC
Cooling	9,000 BTU/h
Outdoor Design Temp. F° DB/WB	95/75
Heating	12,000 BTU/h
Outdoor Design Temperature F° DB/WB	47/43
CFM Cooling - H/ M/ L/ Q	441/376/282/182
CFM Heating - H/ M/ L/ Q	441/376/306/194
Noise Level Cooling db (A) - H/ M/ L/ Q	43/40/32/21
Noise Level Heating db (A) - H/ M/ L/ Q	43/38/33/22
Weight	24 lbs.

Refrigerant Piping:*

Discharge Vapor Line (O.D.)	1/4 in.
Suction (O.D.)	3/8 in.

Standard Features:

- ♦ Minimum Heat
- ♦ Five year parts warranty
- ♦ Digital wireless remote control
- ♦ Auto Louver: Up/Down
- ♦ Apple Catechin / Ion Deodorizing Filters
- ♦ Sleep Timer
- ♦ Auto Restart/ Reset
- ♦ 24 hour timer
- ♦ Quiet Mode
- ♦ Dry mode
- ♦ Refrigerant R410A

*Piping lengths vary by outdoor unit. See outdoor unit submittal sheet for detailed specifications.

OUTLINE AND DIMENSIONS

