## **AOU12RLFW1 Submittal**





## **Inverter Driven Heat Pump**

Job Name:	Approval:	
Location:	Date:	
Engineer:	Construction:	
Submitted to:	Unit #:	
Submitted by:	Drawing #:	
Reference:	<u> </u>	

Outdoor Unit Pour Available Voltage Fuse Size, Max. MCA	e Range	208-230/VAC-1Ph-60Hz 187-253VAC 20A 9.0A
Compressor No. used Output Lubrican Oil	Inverter Drive	en Variable Speed DC Twin Rotary 1 750W POE (VG74)
Ean tuna		Dropollor

No. used			1
Output			750W
Lubrican Oil			POE (VG74)
Fan type Motor Output Airflow rate	Cooling/Heating	(High)	Propeller 50W 1036 / 889CFM
Refrigerant Outdoor unit Control O.D. Discharge O.D Suction	(in) (in)	Ele	R410A 2lbs 5oz ectronic Expansion Valve 1/4"(Flare) 3/8"(Flare)
Dimensions Uncrated	(in) (mm)	,	H x W x D 21-1/4 x 31-1/8 x 11-7/16 (540 x 790 x 290)
Crated	`(in) <sup>′</sup> (mm)		25-1/2 x 36-3/4 x 15-3/4 (648 x 934 x 400)
Weight		•	Outdoor

TTOIGHT	Gatagoi
Net	80lbs (36kg)
Gross Shipping	86lbs (39kg)
Cooling	
Rated Capacity	12,000BTU/h
Min-Max Capacity	3,100~13,300BTU/h
Rated Power Input	0.96kW
Max. Power Input	1.4kW
SEER	22.0
EER	12.5
Outdoor Sound Rating	49dB

Heating	
Rated Capacity	16,000BTU/h
Min-Max Capacity	3,100~19,100BTU/h
Rated Power Input	1.28kW
Max. Power Input	1.99kW
HSPF	11.0
EER	12.5
Outdoor Sound Rating	49dB


Connection method	(Tialeu)
Connection method	(Flared)
Max. Pipe Height Difference	49ft
Max. Piping Length (Total)	66ft
Piping Lengths	


Operating Range	
Cooling	14°F~115°F DB
<u>Heating</u>	5°F~75°F DB


Fujitsu General America, Inc
Fairfield, NJ 07004
Toll Free: 1-888-888-3424
Fax: (973) 836-0447
www.fujitsugeneral.com

Fujitsu products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this data sheet without notice and without incuring any obligations.









Power source of specifications : 230V

Cooling: Indoor temperature of 80°F(26.67°C)DB / 67°F(19.44°C)WB, and outdoor temperature of 95°F(35°C)DB/75°F(23.89°C)WB. Heating: Indoor temperature of 70°F(21.11°C)DB / 60°F(15.56°C)WB, and outdoor temperature of 47°F(8.33°C)DB/43°F(6.11°C)WB. Pipe length: 24ft. 7in.(7.5m),Height difference: 0 ft.(0m) [Outdoor unit - Indoor unit]

