



## Submittal Data Sheet

1.0-Ton Wall Mounted Unit

FTXN12KEVJU5RXN12KEVJU5

### FEATURES

- Low ambient heat operation down to 0° F
- Titanium apatite photocatalytic air purifying
- 10 year limited parts and compressor warranty with online registration

### BENEFITS

- Quiet operation

### INDOOR UNIT



### OUTDOOR UNIT





## Submittal Data Sheet

1.0-Ton Wall Mounted Unit

FTXN12KEVJU5RXN12KEVJU5

### SYSTEM PERFORMANCE

Indoor Unit Model No.	FTXN12KEVJU5	Indoor Unit Name:	FTXN12KEVJU5
Outdoor Unit Model No.	RXN12KEVJU5	Outdoor Unit Name:	RXN12KEVJU5
Rated Cooling Capacity (Btu/hr):	12,000	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Sensible Capacity (Btu/hr):	8,240	Rated Piping Length(ft):	
Max/Min Cooling Capacity (Btu/hr):	12,000 / 4,400	Rated Height Difference (ft):	49.20
Cooling Input Power (kW):	1.210	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 70 Ambient (°F DB/WB): 47 / 43
SEER (Non-Ducted/Ducted):	18.00 /	HSPF (Non-Ducted/Ducted):	8.5 /
EER (Non-Ducted/Ducted):	9.90 /	Heating COP (Non-Ducted/Ducted):	2.9 /
Rated Heating Capacity (Btu/hr):	13,500		
Max/Min Heating Capacity (Btu/hr):	16,400 / 4,400		
Heating Input Power (kW):	1.22		

### SYSTEM DETAILS

Refrigerant Type:	R-410A	Cooling Operation Range (°F DB):	14 - 115
Holding Refrigerant Charge (lbs):	2.2	Heating Operation Range (°F WB):	5 - 77
Additional Charge (lb/ft):	0.22	Max. Pipe Length (Vertical) (ft):	
Pre-charge Piping (Length) (ft):		Cooling Range w/Baffle (°F DB):	0 - 115
Max. Pipe Length (Total) (ft):	66	Heating Range w/Baffle (°F WB):	0 - 77
Max Height Separation (Ind to Ind ft):	49		

# Submittal Data Sheet


1.0-Ton Wall Mounted Unit

FTXN12KEVJU5RXN12KEVJU5

**INDOOR UNIT DETAILS**

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Airflow Rate (H/M/L/SL) (CFM):	328/254/184/152
Power Supply Connections:	L1, L2, Ground	Moisture Removal (Gal/hr):	
Min. Circuit Amps MCA (A):		Gas Pipe Connection (inch):	3/8
Max Overcurrent Protection (MOP) (A):		Liquid Pipe Connection (inch):	1/4
Dimensions (HxWxD) (in):	11-1/8 x 30-1/4 x 7-3/4	Condensate Connection (inch):	5/8
Panel (HxWxD) (in):		Sound Pressure (H/M) (dBA):	42/27
Net Weight (lb):	16	Sound Power Level (dBA):	
Panel Weight (lb):		Ext. Static Pressure (Rated/Max) (inWg):	0.00 / 0.00

## DIMENSIONAL DRAWING - INDOOR UNIT



# Submittal Data Sheet

1.0-Ton Wall Mounted Unit  
FTXN12KEVJU5RXN12KEVJU5

**OUTDOOR UNIT DETAILS**

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Compressor Type:	Inverter
Power Supply Connections:	L1, L2, Ground	Capacity Control Range (%):	-
Min. Circuit Amps MCA (A):	7.00	Airflow Rate (H) (CFM):	921
Max Overcurrent Protection (MOP) (A):	15.00	Gas Pipe Connection (inch):	3/8
Max Starting Current MSC(A):		Liquid Pipe Connection (inch):	1/4
Rated Load Amps RLA(A):	6.1	Sound Pressure (H) (dBA):	50
Dimensions (HxWxD) (in):	21-11/16 x 25-15/16 x 10-3/4	Sound Power Level (dBA):	64
Net Weight (lb):	68		

## DIMENSIONAL DRAWING - OUTDOOR UNIT

